



ProLite T3234MSC-2

ProLite T3234MSC uses Projective Capacitive Touch Technology, built into an eye catching bezel with Edge to Edge glass. Featuring VA LCD Screen technology, it offers exceptional colour performance and wide viewing angles , making it a perfect interactive display for Interactive Digital Signage. In addition to the superb image quality, the screen comes with a rugged bezel making it suitable for demanding environments. The screen also features a vast array of inputs including DVI as well as USB for the Touch sensor itself, and a High Definition 1920 x 1080 Resolution. The ProLite T3234MSC is the ideal solution for Interactive Digital Signage , Instore Retail, Kiosks , Gaming and Interactive Presentations.

DISPLAY CHARACTERISTICS

Diagonal	31.5"
Touchtechnology	projective capacitive, multitouch (2 compatible touch points - HID, supported only under Windows® 7/8), activated by finger
Panel	VA LED-backlit
Glass hardness	7H minimum
Display area h x w	392.8 x 698.4 mm; 15.5" x 27.5"
Response time	6.5 ms
Static contrast	3 000 : 1 with touch panel
Brightness	315 cd/m² with touch panel
Viewing zone	horizontal/vertical: 178° / 178°; right/left: 89° / 89°; up/down: 89° / 89°
Display colour	16.7 million
Pixel pitch h x v	0.364 x 0.364 mm
Native resolution	Full HD 1080p, 1920 x 1080 (2.1 megapixel)
Horizontal sync	31,47 - 67.5 KHz
Vertical sync	47 - 63 Hz
Synchronization	Separate Sync
Aspect ratio	16 : 9
Light transmittance	90%

POWER MANAGEMENT

Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	65 W typical; max. 2 W in Power management mode
Power management	VESA DPMS

DIMENSIONS / WEIGHT

Dimensions w x h x d	781.5 x 476.5 x 69.5 mm
Weight	16.2 kg

INTERFACES / CONNECTORS / CONTROLLERS

Analog input connector	VGA (D-Sub)
Digital input connector	DVI-D
Output connector	RS 232C
Inputs	USB (for touch connectivity), RS 232C
	D-Sub, DVI-D

SPECIAL FEATURES

Plug & Play	VESA DDC2B™
Controls	On-Screen-Display in 8 languages (DE, EN, ES, FR, IT, JP, Chinese - traditional and simplified) and 5 front controls (Menu, Scroll up/ Brightness, Scroll down/ Mute, Select/ Auto, Power)
User controls	contrast, brightness, auto adjust, H.position, V.position, H.size, phase, OSD H.position, OSD V.position, OSD timeout, reset, input select, OSD language, colour temperature, volume, mute
Speakers	2 x 8 W (Stereo)
Safety	CE, TÜV-Bauart, IPX1 (front)
VESA mounting	400 x 200 mm
Colour	Black

ACCESSORIES

Driver	multi-touch: Windows® 7/8, single-touch: Vista (HID compliant)
Included accessories	power cable, VGA (D-Sub) signal cable, DVI-D signal cable, audio cable, USB cable, Touch Panel Driver Disk (CD-ROM), quick start guide, safety guide
Optional accessories	remote OSD key



ProLite T3234MSC-B2X

32" 10 point multi-touch monitor built into an eye catching bezel with Edge to Edge glass

With 1920x1080 Full HD resolution and Projective Capacitive 10 point touch technology, the ProLite T3234MSC-B2X delivers seamless and accurate touch response. Featuring an AMVA PID grade LED LCD screen technology, it offers exceptional colour performance and wide viewing angles, making it a perfect interactive display for Interactive Digital Signage. In addition to the superb image quality, the screen comes with a rugged bezel making it suitable for demanding environments. The screen features a vast array of inputs including DVI as well as USB for the Touch sensor itself. The ProLite T3234MSC-B2X is the ideal solution for Interactive Digital Signage, Instore Retail, Kiosks, Gaming and Interactive Presentations.

DISPLAY CHARACTERISTICS

Diagonal	31.5"
Touchtechnology	projective capacitive, multitouch (10 compatible touch points - HID, only with supported OS), activated by finger
Panel	AMVA LED-backlit
Glass hardness	7H minimum
Display area h x w	392.8 x 698.4 mm; 15.5" x 27.5"
Response time	6.5 ms
Static contrast	3 000 : 1 with touch panel
Brightness	315 cd/m ² with touch panel
Viewing zone	horizontal/vertical: 178° / 178°; right/left: 89° / 89°; up/down: 89° / 89°
Display colour	16.7 million
Pixel pitch h x v	0.364 x 0.364 mm
Native resolution	Full HD 1080p, 1920 x 1080 (2.1 megapixel)
Horizontal sync	31,47 - 67.5 KHz
Vertical sync	47 - 63 Hz
Synchronization	Separate Sync
Aspect ratio	16 : 9
Light transmittance	90%

POWER MANAGEMENT

Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	65 W typical; max. 2 W in Power management mode
Power management	VESA DPMS

DIMENSIONS / WEIGHT

Dimensions w x h x d	781.5 x 476.5 x 69,5 mm
Weight	16.2 kg

INTERFACES / CONNECTORS / CONTROLLERS

Analog input connector	VGA (D-Sub)
Digital input connector	DVI-D
Output connector	RS 232C
Inputs	USB (for touch connectivity), RS 232C
	D-Sub, DVI-D

SPECIAL FEATURES

Plug & Play	VESA DDC2B™
Controls	On-Screen-Display in 8 languages (DE, EN, ES, FR, IT, JP, Chinese - traditional and simplified) and 5 front controls (Menu, Scroll up/ Brightness, Scroll down/ Mute, Select/ Auto, Power)
User controls	contrast, brightness, auto adjust, H.position, V.position, H.size, phase, OSD H.position, OSD V.position, OSD timeout, reset, input select, OSD language, colour temperature, volume, mute
Speakers	2 x 8 W (Stereo)
Safety	CE, TÜV-Bauart, IPX1 (front)
VESA mounting	400 x 200 mm
Colour	Black
Orientation	landscape/portrait

ACCESSORIES

Driver	multi-touch: Windows® 7/8, single-touch: Vista (HID compliant)
Included accessories	power cable, VGA (D-Sub) signal cable, DVI-D signal cable, audio cable, USB cable, Touch Panel Driver Disk (CD-ROM), quick start guide, screw (M3x6mm), safety guide
Optional accessories	remote OSD key



ProLite TH4264MIS-1

ProLite TH4264MIS a 42" Full HD professional large format display with touch screen functionality

Incorporating the new InfraRed 6 point touch feature along with our supreme panel colour performance, this display offers the optimum performance for a truly multi-user interactive display experience. With the ability to handle up to 6 individual touch points, the TH4264MIS offers an exceptional capacity within Retail, Education, Training, Corporate and B2B markets. Features include PIP and PBP perfect for Video Conferencing or handing multi-input content in many environments. Landscape and Portrait friendly, the display can be mounted according to the application for true impact in Interactive Digital Signage and with Protection Glass the display can handle harshest environments from the Classroom to Public Domain Retail installation

DISPLAY CHARACTERISTICS

Diagonal	42"
Touchtechnology	infrared, multitouch (6 compatible touch points - HID, supported only under Windows® 7/8), activated by finger or pen
Panel	IPS, LED-Backlit
Display area h x w	522 x 927.9 mm; 20.6" x 36.5"
Response time	9 ms
Static contrast	1 000 : 1 with touch panel
Brightness	400 cd/m² with touch panel
Viewing zone	horizontal/vertical: 178° / 178°; right/left: 89° / 89°; up/down: 89° / 89°
Display colour	16.7 million
Pixel pitch h x v	0.4833 x 0.4833 mm
Native resolution	Full HD 1080p, 1920 x 1080 (2.1 megapixel)
Horizontal sync	30 - 83 KHz
Vertical sync	50 - 76 Hz
Synchronization	Separate Sync
Aspect ratio	16 : 9
Light transmittance	88%
Max. non-stop operating time	18 hours/day (IRFM on)

POWER MANAGEMENT

Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	119 W typical; max. 0.5 W in Power management mode
Power management	VESA DPMS

DIMENSIONS / WEIGHT

Dimensions w x h x d	980.5 x 570 x 121 mm
Weight	23 kg

INTERFACES / CONNECTORS / CONTROLLERS

Analog input connector	VGA (D-Sub), RCA (VIDEO), S-Video, BNC jack, mini jack
Digital input connector	DVI-D, HDMI, DisplayPort
HDCP	yes
Audio-signal-input	mini jack, RCA L/R(2x)
Output connector	RS232C, RCA (L/R), VGA (D-Sub), BNC jack (VIDEO)
Inputs	RS232C, RCA (L/R), mini jack, BNC jack, S-Video, USB (for touch connectivity), RJ45 (for LAN control)
	D-Sub, DVI-D, HDMI, DisplayPort

SPECIAL FEATURES

Plug & Play	VESA DDC2B™
Controls	On-Screen-Display in 7 languages (EN, FR, ES, NL, DE, PL, RU) controlled by back controls or a remote control
User controls	picture (picture mode, backlight, contrast, brightness, chroma, phase, sharpness, colour temp., noise reduction, film mode, rest), sound (sound mode, treble, bass, balance, surround, speaker, audio source, reset), screen (PAP setting, display wall, aspect, adjust screen, freeze, touch feature), setting (language, schedule, power save, control setting, network settings, set monitor ID, HDMI control, advanced, information, reset all)
Speakers	2 x 12 W (Stereo)
Safety	CE, TÜV-Bauart, CB, CU
VESA mounting	400 x 200 mm
Colour	Black
Remote control	yes
Orientation	portrait/landscape

ACCESSORIES

Driver	multi-touch: Windows® 7/8, Android (limited support), Linux and Mac (HID compliant), single-touch: Vista, XP
Included accessories	power cable, VGA (D-Sub) signal cable, DVI-D signal cable, USB cable, remote control, touch pen, iiyama logo sticker, quick start guide, safety guide



ProLite TH4664MIS-1

ProLite TH4664MIS - 46" Full HD professional large format display with 6 compatible touch points

Incorporating the new InfraRed 6 point touch feature along with supreme AMVA3 panel colour performance, this display offers the optimum performance for a truly multi-user interactive experience. With the ability to handle up to 6 individual touch points, the TH4664MIS offers an exceptional capacity within Retail, Education, Training, Corporate and B2B markets. Features include PIP and PBP perfect for Video Conferencing or handing multi-input content in many environments. Landscape and Portrait friendly, the display can be mounted according to the application for true impact in Interactive Digital Signage and with Protection Glass the display can handle harshest environments from the Classroom to Public Domain Retail installation.

DISPLAY CHARACTERISTICS

Diagonal	46"
Touchtechnology	infrared, multitouch (6 compatible touch points - HID, supported only under Windows® 7/8), activated by finger or pen
Panel	AMVA3 LED
Display area h x w	572.67 x 1018.08 mm; 22.5" x 40.1"
Response time	6.5 ms
Static contrast	4 000 : 1 typical
Advanced contrast	40 000 : 1 ACR
Brightness	500 cd/m² typical
Viewing zone	horizontal/vertical: 178° / 178°; right/left: 89° / 89°; up/down: 89° / 89°
Pixel pitch h x v	0.53025 x 0.53025 mm
Native resolution	Full HD 1080p, 1920 x 1080 (2.1 megapixel)
Synchronization	Separate Sync
Aspect ratio	16 : 9
Display colours	1.073 billion (8 bit + FRC)
Light transmittance	88%
PIP (Picture in Picture)	PIP, PBP
Max. non-stop operating time	18 hours/day (IRFM on)

POWER MANAGEMENT

Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	132 W typical; max. 0.5 W in Power management mode
Power management	VESA DPMS

DIMENSIONS / WEIGHT

Dimensions w x h x d	1065.5 x 621 x 100 mm
Weight	28 kg

INTERFACES / CONNECTORS / CONTROLLERS

Analog input connector	VGA (D-Sub), RCA (VIDEO), S-Video, BNC jack, mini jack
Digital input connector	DVI-D, HDMI, DisplayPort
HDCP	yes
Audio-signal-input	mini jack, RCA L/R(2x)
Output connector	RS232C, RCA (L/R), VGA (D-Sub), BNC jack (VIDEO)
Inputs	RS232C, RCA (L/R), mini jack, BNC jack, S-Video, USB (for touch connectivity), RJ45 (for LAN control)
	D-Sub, DVI-D, HDMI, DisplayPort

SPECIAL FEATURES

Plug & Play	VESA DDC2B™
Controls	On-Screen-Display in 7 languages (EN, FR, ES, NL, DE, PL, RU) controlled by back controls or a remote control
User controls	picture (picture mode, backlight, contrast, brightness, chroma, phase, sharpness, colour temp., noise reduction, film mode, rest), sound (sound mode, treble, bass, balance, surround, speaker, audio source, reset), screen (PAP setting, display wall, aspect, adjust screen, freeze, touch feature), setting (language, schedule, power save, control setting, network settings, set monitor ID, HDMI control, advanced, information, reset all)
Speakers	2 x 12 W (Stereo)
Safety	CE, TÜV-Bauart, CB, GOST-R
VESA mounting	400 x 200 mm
Colour	Black
Remote control	yes
Orientation	portrait/landscape

ACCESSORIES

Driver	multi-touch: Windows® 7/8, Android (limited support), Linux and Mac (HID compliant), single-touch: Vista, XP
Included accessories	power cable, VGA (D-Sub) signal cable, DVI-D signal cable, USB cable, remote control, touch pen, iiyama logo sticker, quick start guide, safety guide



ProLite TH5563MIS

ProLite TH5563MIS is a 55" Full HD professional, feature-rich and robust LED-backlit display with touch functionality (**infrared - 6 compatible touch points**). Incorporating the latest Commercial Grade 120Hz IPS panel technology, the display guarantees great viewing from all angles, high brightness and exceptional colour clarity. It also features an ambient light sensor delivering optimal picture quality with the added benefit of saving on power. The display supports PIP, a video-wall function and incorporates a wide range of video and audio inputs which ensures compatibility with multiple platforms. ProLite TH5563MIS is prepared for easy installation using the VESA wall mount. This display will suit a wide range of applications including Interactive Signage, Retail, Exhibitions, Kiosks, Education and Training, Conference Centres and Presentations.

DISPLAY CHARACTERISTICS

Diagonal	55"
Touchtechnology	infrared, multitouch (6 compatible touch points - HID, supported only under Windows® 7/8), activated by finger or pen
Panel	IPS, LED-Backlit
Display area h x w	680.4 x 1209.6 mm; 26.8" x 47.6"
Response time	12 ms
Static contrast	1 300 : 1 typical
Brightness	450 cd/m² typical
Viewing zone	horizontal/vertical: 178° / 178°; right/left: 89° / 89°; up/down: 89° / 89°
Pixel pitch h x v	0.63 x 0.63 mm
Native resolution	Full HD 1080p, 1920 x 1080 (2.1 megapixel)
Horizontal sync	30 - 75 KHz
Vertical sync	50 - 75 Hz
Synchronization	Separate Sync
Aspect ratio	16 : 9
Display colours	1.073 Billion (10bit)
Light transmittance	88%
PIP (Picture in Picture)	large, medium, small
Max. non-stop operating time	18 hours/day (IRFM on)

POWER MANAGEMENT

Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	136 W typical; max. 0.5 W in Power management mode
Power management	VESA DPMS

DIMENSIONS / WEIGHT

Dimensions w x h x d	1273 x 743.5 x 96 mm
Weight	45 kg

INTERFACES / CONNECTORS / CONTROLLERS

Analog input connector	VGA (D-Sub), RCA (VIDEO), S-Video
Digital input connector	DVI-D, HDMI
HDCP	yes
Audio-signal-input	PC-AUDIO, RCA L/R(2x)
Output connector	RCA (L/R), RS232, VGA (D-Sub), RCA (VIDEO)
Inputs	RS232C, USB (for touch connectivity) D-Sub, DVI-D, HDMI

SPECIAL FEATURES

Plug & Play	VESA DDC2BTM
Controls	On-Screen-Display in 7 languages (EN, FR, ES, NL, DE, PL, RU) controlled by back controls or a remote control
User controls	picture (picture mode, contrast, brightness, colour, tint, sharpness, backlight, ACR, colour temp.), sound (volume, mute, audio source, speaker), option (aspect ratio, PIP, video source, auto adjust, clock, phase, H.position, V.position, ambient light sensor, auto detection, touch feature), setting (language, schedule, display wall, power save, set monitor ID, image retention, auto adjust, advanced (restore, OSD info box))
Speakers	2 x 12 W (Stereo)
Safety	CE, TÜV-Bauart, CB
VESA mounting	200 x 400 mm
Colour	Black
Remote control	yes
Orientation	portrait/landscape

ACCESSORIES

Driver	multi-touch: Windows® 7/8 (HID compliant), single-touch: Vista, XP, 9X, 2000, CE, NT4), Linux, Mac (OSX)
Included accessories	power cable, VGA (D-Sub) signal cable, remote control, touch pen, iiyama logo sticker, quick start guide, safety guide



ProLite TH5563MIS-B1AG

ProLite TH5563MIS is a 55" Full HD professional, feature-rich and robust LED-backlit display with touch functionality (**infrared - 6 compatible touch points**) and AG Coating. The Anti Glare coating is used in professional-grade displays to help avoid issues with reflections and external light sources affecting colour reproduction, contrast and sharpness. It also makes the screen less susceptible to dust, grease and dirt marks. Incorporating the latest Commercial Grade 120Hz IPS panel technology, the display guarantees great viewing from all angles, high brightness and exceptional colour clarity. It also features an ambient light sensor delivering optimal picture quality with the added benefit of saving on power. The display supports PIP, a video-wall function and incorporates a wide range of video and audio inputs which ensures compatibility with multiple platforms. ProLite TH5563MIS will suit a wide range of applications including Interactive Signage, Retail, Exhibitions, Kiosks, Education and Training, Conference Centres and Presentations.

DISPLAY CHARACTERISTICS

Diagonal	55"
Touchtechnology	infrared, multitouch (6 compatible touch points - HID, supported only under Windows® 7/8), activated by finger or pen
Panel	IPS, LED-Backlit, AG80 Coated Glass
Display area h x w	680.4 x 1209.6 mm; 26.8" x 47.6"
Response time	12 ms
Static contrast	1 300 : 1 typical
Brightness	450 cd/m² typical
Viewing zone	horizontal/vertical: 178° / 178°; right/left: 89° / 89°; up/down: 89° / 89°
Pixel pitch h x v	0.63 x 0.63 mm
Native resolution	Full HD 1080p, 1920 x 1080 (2.1 megapixel)
Horizontal sync	30 - 75 KHz
Vertical sync	50 - 75 Hz
Synchronization	Separate Sync
Aspect ratio	16 : 9
Display colours	1.073 Billion (10bit)
Light transmittance	88%
PIP (Picture in Picture)	large, medium, small
Max. non-stop operating time	18 hours/day (IRFM on)

POWER MANAGEMENT

Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	136 W typical; max. 0.5 W in Power management mode
Power management	VESA DPMS

DIMENSIONS / WEIGHT

Dimensions w x h x d	1273 x 743.5 x 96 mm
Weight	45 kg

INTERFACES / CONNECTORS / CONTROLLERS

Analog input connector	VGA (D-Sub), RCA (VIDEO), S-Video
Digital input connector	DVI-D, HDMI
HDCP	yes
Audio-signal-input	PC-AUDIO, RCA L/R(2x)
Output connector	RCA (L/R), RS232, VGA (D-Sub), RCA (VIDEO)
Inputs	RS232C, USB (for touch connectivity) D-Sub, DVI-D, HDMI

SPECIAL FEATURES

Plug & Play	VESA DDC2BTM
Controls	On-Screen-Display in 7 languages (EN, FR, ES, NL, DE, PL, RU) controlled by back controls or a remote control
User controls	picture (picture mode, contrast, brightness, colour, tint, sharpness, backlight, ACR, colour temp.), sound (volume, mute, audio source, speaker), option (aspect ratio, PIP, video source, auto adjust, clock, phase, H.position, V.position, ambient light sensor, auto detection, touch feature), setting (language, schedule, display wall, power save, set monitor ID, image retention, auto adjust, advanced (restore, OSD info box))
Speakers	2 x 12 W (Stereo)
Safety	CE, TÜV-Bauart, CB
VESA mounting	200 x 400 mm
Colour	Black
Remote control	yes
Orientation	portrait/landscape

ACCESSORIES

Driver	multi-touch: Windows® 7/8, Android, Linux and Mac (HID compliant), single-touch: Vista, XP
Included accessories	power cable, VGA (D-Sub) signal cable, DVI-D signal cable, remote control, touch pen, iiyama logo sticker, quick start guide, safety guide



ProLite TH6564MIS-B1AG

A professional display with IR touch-technology, suitable for educational needs

The ProLite TH6564MIS is the perfect solution for educational and corporate use. The high quality commercial AMVA3 LCD screen guarantees great viewing angles from all sides and delivers superb image performance from anywhere in a class or meeting-room. The solid and robust design is capable of withstanding the requirements of the most demanding environments. Unlike interactive whiteboards, there are no shadows or reductions in image performance to contend with. The Anti Glare screen drastically reduces ambient reflection in high brightness environments without compromising the sharp clarity of the content. By using a finger or stylus, you can write, annotate, draw and present with confidence.

DISPLAY CHARACTERISTICS

Diagonal	65"
Touchtechnology	infrared, multitouch (2 compatible touch points) activated by finger or pen, no pressure required to generate touch
Panel	AMVA3 LED-backlit, AG Coated Glass
Display area h x w	803.52 x 1428.48 mm; 31.6" x 56.2"
Response time	8 ms
Static contrast	4 000 : 1 with touch panel
Brightness	450 cd/m ² with touch panel
Viewing zone	horizontal/vertical: 178° / 178°; right/left: 89° / 89°; up/down: 89° / 89°
Pixel pitch h x v	0.744 x 0.744 mm
Native resolution	Full HD 1080p, 1920 x 1080 (2.1 megapixel)
Horizontal sync	30 - 83 KHz
Vertical sync	50 - 76 Hz
Synchronization	Separate Sync
Aspect ratio	16 : 9
Display colours	1.073 G (8bit+Hi-FRC)
Light transmittance	88%
PIP (Picture in Picture)	PIP and PBP
Max. non-stop operating time	18 hours/day

POWER MANAGEMENT

Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	265 W typical; max. 0,5 W in Power management mode
Power management	VESA DPMS

DIMENSIONS / WEIGHT

Dimensions w x h x d	1521 x 833 x 107.5 mm
Weight	63.5 kg

INTERFACES / CONNECTORS / CONTROLLERS

Analog input connector	VGA (D-Sub), Video, S-Video, RCA
Digital input connector	DVI-D, HDMI, DisplayPort
Audio-signal-input	PC-Audio, RCA L/R
Output connector	Audio, VGA (D-Sub), RS232C, Video, RJ45
Inputs	USB (touch), RS232C & LAN (control)

SPECIAL FEATURES

Plug & Play	VESA DDC2BTM
Controls	On-Screen-Display in 7 languages (EN, FR, ES, NL, DE, PL, RU) controlled by side controls or a remote control
User controls	picture (picture mode, backlight, contrast, brightness, chroma, phase, sharpness, colour temp., noise reduction, film mode, reset), sound (sound mode, treble, bass, balance, surround, speaker, audio source, reset), screen (PAP setting, display wall, aspect, adjust screen, freeze, touch feature), setting (language, schedule, power save, control setting, network settings, set monitor ID, HDMI control, advanced, information, reset)
Speakers	2 x 12 W (Stereo)
Safety	CE, TÜV-Bauart, CB, CU
VESA mounting	400 x 400 mm
Colour	Black
Remote control	yes
Orientation	landscape/portrait

ACCESSORIES

Driver	single-touch: Windows 98 / NT / 2000 / XP / Vista / 7, Mac OS, Linux, multi-touch: Windows® 7/8
--------	---



www.logiscenter.com
902 050 030



www.logiscenter.it
02 479 216 97



www.logiscenter.de
info@logiscenter.de



www.logiscenter.pt
308 800 842

About LOGISCENTER

Grupo Logiscenter is the leading provider in Europe of automatic identification and data capture equipments. Our products include barcode printing and reading devices, mobile computing devices, wireless access points, identification cards, and consumables.

Reasons to work with us

Our customers come first. Our objective is not only selling our products but also holding a long-lasting relationship with our customers, based on the benefits and advantages we create for you and your company.

The best brands. We offer products from the best manufacturers worldwide.

Expert technical support team. Our support staff are experts in the products we sell. But not just the products, they can tell you the best solution for your particular problem or need.

Largest stock. We have a permanent stock of more than 12,000 products.

Same-day shipping. For all orders placed and confirmed before 16:00 on working days.

Best prices. With Logiscenter, you can be sure that you are paying a fair price for your products we will not overcharge you.

Easy returns. Damaged or defective products can be returned easily, for an exchange or reimbursement.

Our Brands



MOTOROLA



Intermec®

Honeywell®

DATALOGIC™



datamax • o'neil

Metrologic

LXE

EPSON®

elo

star

unitech

PRINTRONIX

symbol®



**All Brands
Technical Service**


Solutions for: Industry • Consumer • Mobility Transportation and Logistics • Retail • Health



Label printers



Barcode readers



Data terminals & PDA



PVC card printers



RFID



Consumables
(labels, ribbons, PVC cards)